

**New**

# PosiTest<sup>®</sup> **DFT**

## Coating Thickness Gauge

### *Ideal for...*

- Powder Coaters
- Paint Applicators
- Coating Inspectors
- Painting Contractors
- Automotive Refinishers

### *2 Models...*

**Ferrous** for STEEL

**Combo** for ALL METALS



simply  
measures

**BLASTMASTER<sup>®</sup>**



# PosiTest<sup>®</sup> DFT

## Coating Thickness Gauge



Actual Size

### Two Models

- **PosiTest<sup>®</sup> DFT Ferrous**  
measures non-magnetic coatings on steel.
- **PosiTest<sup>®</sup> DFT Combo**  
measures both non-magnetic coatings on steel AND non-conductive coatings on aluminum, brass, etc. **Automatically** recognizes the substrate and takes a measurement.

### Features

- Fast, repeatable measurements
- No calibration required for most applications
- ZERO feature for rough or curved surfaces
- Handy RESET feature when no zero reference is available
- Strong, wear-resistant, ruby-tipped probe
- Audible and visible measurement indication
- V-groove in probe for positioning on cylindrical parts
- Mills/Microns switchable
- Basic instructions on the back of each gauge

### Specifications

Measurement Range	0 – 40 mils	0 – 1000 μm
Accuracy	±(0.1 mils + 3%)	±(2μm + 3%)
Size	4 x 1.5 x 0.9 in.	100x38x23 mm
Weight	2.5 oz.	70 g



Gauge Comes Complete with built-in probe, plastic shims, hard shell storage case, AAA battery, instructions and one (1) year warranty.

Conforms to: ISO 2178/2360/2808, prEN ISO 19840, ASTM B244/B499/B659/D1186/D1400/E376/G12, BS3900-C5, SSPC-PA2 and others. Certificate of Calibration traceable to NIST available.

Blastmaster  
3 Bruce Avenue  
PO Box 1144  
Marleston 5033  
South Australia

**Telephone**  
**Fax:**  
**Toll Free:**  
  
**Email:**  
**Web:**

08 8292 2000  
08 8292 2001  
1800 882 229  
1800 BLAST-IT  
sales@blastmaster.com.au  
www.blastmaster.com.au

# BLASTMASTER<sup>®</sup>

